

ISO-BLOCO 600

**Product description**

ISO-BLOCO 600 is a PUR sealing tape impregnated with polymer dispersion. It is specially designed for reliable joint sealing in high rise buildings and facades up to 100 m high. Being a quality-tested BG 1 sealing tape, ISO-BLOCO 600 fulfils the stringent requirements of the DIN 18542 edition 2009. In addition to providing protection against driving rain to a minimum of 600 Pa (equivalent to wind force 11 - Violent Storm) ISO-BLOCO 600 also possesses outstanding thermal and acoustic characteristics.

Certifications**Application range**

For sealing construction joints (including moving joints) between

- > Prefabricated concrete
- > Outer frames and masonry
- > Skylights
- > Perimeter seals for fenestration

For areas including

- > Trapezoidal profiled sheets, sandwich and metal panels
- > Prefabricated elements made of concrete and other materials
- > Solid, timber and dry wall construction
- > Window installation

Benefits

- > Complies with the DIN 18542 BG 1
- > Reliability through a wider joint application range
- > Seals against wind, dust, splash water and driving rain
- > Vapour diffusion permeable
- > Good adhesive properties, to aid installation
- > Permanently elastic with long-term movement absorption
- > Thermal and acoustic insulation
- > Can be painted over with standard emulsion paints
- > Applications in all construction areas and building types are possible
- > CE-certified (ETA-07/0072)
- > Constant quality control according to DIN standards, with regular controls from independent institutions
- > Externally monitored by ift Rosenheim: for driving rain and air permeability (a-value)
- > 10-year performance warranty
(on the conditions of the manufacturer; available upon request)

Product online

Order description	Dimension joint depth x width [mm]	Box content [rolls]	Metres per roll [m]	PU [m]	Price/100 m [EUR]	Article number	EAN
ISO-BLOCO 600 15 / 1-4	15 / 1-4	20	13.0	260		0060015104	4048368254945
ISO-BLOCO 600 15 / 2-6	15 / 2-6	20	12.0	240		0060015206	4048368254983
ISO-BLOCO 600 15 / 4-9	15 / 4-9	20	8.0	160		0060015409	4048368255010
ISO-BLOCO 600 20 / 1-4	20 / 1-4	15	13.0	195		0060020104	4048368254952
ISO-BLOCO 600 20 / 2-6	20 / 2-6	15	12.0	180		0060020206	4048368254990
ISO-BLOCO 600 20 / 4-9	20 / 4-9	15	8.0	120		0060020409	4048368255027

* Movement of structural elements and temporary changes in length of existing joints have to be taken into account for the suitable tape dimensions.