

## DEKTITE® Square (set)



### Application range

- > For waterproofing pipes on trapezoidal or sinusoidal metal roofs or corrugated fibre cement roofs

### Properties

- > Version EDPM (black)
- > Temperature resistance EPDM (black or grey) permanent 50 °C to +115 °C, short-term up to +150 °C
- > Temperature resistance silikone (red) permanent 50 °C to +200 °C, short-term up to +250 °C

### Included in delivery (set parts)

- 1 pipe flashing
- 1 cartridge of EJOPLAST joint sealant
- 1 self-drilling screw set - optionally folding blind rivet set

### Cross references

Hose clamp  
Tightener  
Joint sealant

### Benefits


- > Perfect seal on roof and facade
- > No interference of thermal elongation of pipes
- > No fatigue fractures
- > 20-year warranty on material

### Note


Use folding blind rivets for fibre cement boards. Profile height max. 45 mm.



1. Adjust DEKTITE® to the pipe.




2. Adjust DEKTITE® to the profiled sheet and mark.



3. Apply sealant.



4. Adjust DEKTITE® to the shape of the profiled sheet.



5. Fasten DEKTITE® with self-drilling screws or folding blind rivets.

## Further versions available



DEKTITE®  
Premium 3

### Product online



Order description	For pipe diameter [mm]	Base [mm]	Roof pitch [°]	Content Cartridge [ml]	Content screw [pieces]	PU [set]	Price/1 [EUR]	Article number	EAN
DFE 100 B	0–35	100 x 100	0–60	80	8	1		8200004704	4061245013954
DFE 101 B	5–55	139 x 139	0–35	80	8	1		8200104704	4061245013800
DFE 103 B	5–127	221 x 221	0–35	80	16	1		8200304704	4061245013787
DFE 104 B	75–175	280 x 280	0–35	80	20	1		8200404704	4061245013763
DFE 106 B	125–230	363 x 363	0–35	80	28	1		8200604704	4061245013749
DFE 107 B	150–300	456 x 456	0–35	310	32	1		8200704704	4061245013725
DFE 109 B	230–508	681 x 681	0–35	310	40	1		8200904704	4061245013701

**Order information: All versions also available in grey (EPDM) and red (silicone) Further lengths upon request.**